



**INTERMEDIATE PRESSURE LIMITS**  
 INTERMEDIATE PRESSURES MUST BE BETWEEN  
 128-140 PSIG AT BOTH 300 AND 2,000 PSIG  
 WITH A MAXIMUM OF 8 PSIG DIFFERENCE BETWEEN  
 THE INTERMEDIATE PRESSURES TAKEN AT 300 AND  
 2,000 PSIG, 0 PSIG INTERMEDIATE PRESSURE  
 CREEPAGE ALLOWED AFTER SEATING OF A NEW SEAT.

ITEM NO.	QTY.	PART NUMBER	DESCRIPTION	SUGG. RETAIL
1	1	10-101-141	BODY, 7/16 H.P. THD.	18.00
2	1	10-101-111	1 ST STAGE INLET PROTECTOR	2.50
3	1	10-101-131	YOKE, 9/16 THD	10.00
4	1	10-101-106	SEAT RETAINER	3.75
5	2	01-050-165	O-RING (RED)	.40
6	1	10-101-105	SEAT	2.50
7	1	10-101-107	SADDLE	5.00
8	1	10-107-111	ADAPTER, FRENCH	1.50
9	2	01-050-144	O-RING (BLUE)	.40
10	1	01-073-101	RETAINER	.40
11	1	01-028-101	FILTER	.80
12	1	10-101-108	YOKE RETAINER	3.00
13	4	01-050-132	O-RING (BLUE)	.40
14	3	01-060-101	WASHER	.40
15	1	10-101-002	SPRING	4.25
16	3	10-101-104	PLUG	1.20
17	3	10-101-006	PLUG W/O-RING	1.40
18	1	10-080-101	CAP (S.P.E.C.)	13.00
19	1	01-050-177	O-RING (BLUE)	.40
20	1	10-101-003	PISTON	15.00
21	2	10-101-039	PLUG W/O-RING, 7/16 THD.	1.40
22	1	10-101-139	PLUG, H.P. 7/16 THD.	1.20
23	3	01-050-138	O-RING (BLUE)	.40
24	1	01-050-342	O-RING (PURPLE)	.40
25	1	10-101-144	ADAPTER (HAS LG. MALE & SM. FEMALE THDS.)	2.50
26	1	10-101-044	ADAPTER W/O-RING (HAS LG. MALE & SM. FEMALE THDS.)	2.70
27	1	10-101-138	ADAPTER (HAS SM. MALE & LG. FEMALE THDS.)	2.50
28	1	10-101-132	YOKE SCREW, 9/16 THD	4.25
28	1	10-101-113	YOKE SCREW, 7/16 THD	3.00
28	1	10-101-130	YOKE SCREW, 3/8 THD	2.50
29	1	10-101-038	ADAPTER W/O-RING (HAS SM. MALE & LG. FEMALE THDS.)	2.70
30	1	01-050-147	O-RING (PURPLE)	.40
1	1	45-101-187	MANUAL	1.00
1	1	10-080-010	KIT, S.P.E.C. CAP & SILICONE GREASE	15.00
1	1	41-035-000	SILICONE GREASE, 7 GR	2.00
1	1	10-080-000	FIRST STAGE COMPLETE	100.00

PRICES SUBJECT TO CHANGE WITHOUT NOTICE.

NOTES:

- NOT SHOWN      ◆ ANNUAL REPLACEMENT
- △ OPTIONAL ITEM      < > TORQUE IN INCH POUNDS
- △ OLDER CONFIGURATION
- △ FOR OLDER CONFIGURATION H.P. HOSE USED W/ NEW CONFIGURATION REGULATORS.
- △ ITEM NOT COVERED UNDER WARRANTY
- △ MAXIMUM 3 WASHERS P/N 01-060-101 WASHERS ARE USED AS SHIMS TO ADJUST THE INTERMEDIATE PRESSURE TO BE WITHIN THE SPECIFIED LIMITS.
- ◆ DYNAMIC O-RING REPLACE ANNUALLY

MARK VIII 4 PORT FIRST STAGE REGULATOR

**SCUBAPRO**

CAT. NO. 10-080-000

A	NOV. 81	CONFIGURATION 1
REV.	DATE	